

RF320I4B-N

Universal transmitter Brown RF433 MHz

Each RF receiver monitors the alarm, battery, tamper and supervisory status of each transmitter. In addition it reports any change in status to the panel, which takes action according to the programmed zone types.



Details

- Learn-Mode Technology
- More than 3 years battery life
- 2 internal reed switches allow for vertical or horizontal mounting
- Wall and cover tamper
- Jumper to select one of the 2 reed switcher or the supervised external input

RF320I4B-N

Universal transmitter Brown RF433 MHz

Technical specifications

General

Application type	Surface mount
------------------	---------------

Wired/wireless

Wired-wireless	Wireless
Wireless frequency	433 MHz legacy
Open-air range	150 m
Operating gap	10 mm max.

Electrical

Batteries	1 x 3,6V Lithium
Battery lifetime	3 to 5 years

Physical

Physical dimensions	32 x 32 x 102 mm
Dimensions contact / sensor	32 x 32 x 102 mm
Net weight	44 g
Colour	Brown

Environmental

Operating temperature	-34° to +60° C
Relative humidity	0 to 90% noncondensing



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:53