

CAMERA TESTER WITH 7" TOUCH SCREEN & DIGITAL CABLE TRACER

Titus

CODE: TITUS-TEST-7-6IN1-HS-WT



Cable Tracer	Tracing Technology	Tone Generator
	RJ45 TDR Testing	Cable Pair Status, Length, Attenuation, Reflectivity & Skew (up to 180m)
	Improvement Testing	UTP & Telephone Cable (etc.) Order & Connectivity Test
Display		7" IPS Touch Screen
Screen Resolution		1280 x 800
CVBS Test Features		1-Channel BNC Input & 1-Channel BNC Looped Output
		Analogue Camera Testing
		PTZ Control; RS485 Control
		Baud 600-115200bps; Compatible with Over 30 Protocols (Including PELCO-D/P, Samsung & Panasonic)
IP Camera Test Features (Up to 8K (32MP) / H.265 / H.264)		CVBS Loop Testing (For Checking BNC Cables)
		IP Discovery; Quick ONVIF; IPC Test; RTSP Play; Auto HD Recognition
		Rapid Video (Auto-View & Test Report Creation)
	Hikvision Testing	Activate Camera, Modify Username, Modify Password & IP Parameters
Coaxial HD Test	Dahua Testing	Test Dahua Cameras, Modify Username, Modify Password & IP Parameters
	4K TVI Camera Test	3840 x 2160px Resolution Support at 15fps (UTC Control & OSD Menu)
	4K CVI Camera Test	3840 x 2160px Resolution Support at 12.5/5fps (UTC Control & OSD Menu)
	4K AHD Camera Test	3840 x 2160px Resolution Support at 15fps (UTC Control & OSD Menu)

CAMERA TESTER WITH 7" TOUCH SCREEN & DIGITAL CABLE TRACER



CODE: TITUS-TEST-7-6IN1-HS-WT

HDMI Input	1 Channel HDMI Input (1080P Support)
Image Zoom	4x
Analogue Video Out	1CH PAL/NTSC Colour Bar Video Signal for Testing Monitors or Video Cables
DC12V Power	DC12V / 3A Power Output
DC24V Power	DC24V / 2A Power Output
PoE Power Output	48V PoE Power (Upto 24W)
UTP Cable Test	Status Displayed on Screen
Simultaneous Tester Play	Screen Projection; Mobile Phone (Android Only); PC Display
Network Test	Trace Route; Monitor Link; DHCP Server; Port-Flash; Ping Test
Wi-Fi	Functionality Built-In (150m Transmission)
Audio Test	1-Channel Audio Signal Input to Test Sound Functionality; 1-Channel Audio Signal to Connect Headphones
PoE Test	Measures a PoE Switch or PSE Power Supply for Voltage and Connection Status
Drop-Down Menu	Select PoE Power Switch; IP Settings; CVBS; LAN info.; HDMI Functions etc.
External Power Supply	DC 12V 2A
Battery	Built-In 7.6V Lithium Polymer Battery (7800mAh)
Recharge	Works for Around 16 Hours on 3.5 to 4 Hours Charge
Operation Settings	OSD Menu for Language Selection: English; French; Italian; Spanish; Polish; Russian; Chinese; Korean; Japanese etc.
Auto Power-Off	1 to 30 Minutes (Programmable)
Working Temperature	-10°C to +50°C (14°F to +122°F)
Working Humidity	30% to 90% (RH)
Dimensions (Main Tester)	240mm x 154mm x 46mm
Net Weight (Main Tester)	620g
Contents	1x Camera Tester (7" Touch Screen) 1x Digital Network Cable Tracer 1x DC12V 2A Adaptor 1x Polymer Lithium Ion Battery (7.6V DC, 7800mAh) 1x Tool Bag (DC Power Cable, BNC Cable, RS485 Cable, Audio Cable & Safety Cord)